2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223

Tel: (65) 64442678 Fax: (65) 67437172

Email: marketing@douyee.com.sg Website: www.douyee.com

## **Product Data Sheet**

PRODUCT CODE / PART NUMBER: DY6008-HS433-BLACK-1G-EVA/RUBBER-S3 SRC-SK-SIZE



BRAND NAME: **EUROSTAT**® Safetykey

## **FEATURES:**

This safety shoe is made of Black Glossy Leather, Black Action Leather and TPU upper, Steel Toe Cap, Composite Midplate, Grey Anti-Odor/Anti-Fatigue PU Insole, EVA Midsole and Nitrile Rubber (NBR) Outsole

**PRODUCT:** Static Dissipative Safety Shoes, Black

- 200J Impact Resistance
- 15KN Compression Resistance
- 1100N Penetration Resistance
- Light Weight, Excellent Comfort
- Resistant to Oil and Most Chemicals
- Non-Marking and Slip Resistant Outsole (SRC)





## **Specifications**

Item	Properties / Typical Values	Test Method
Materials	Upper : Black Glossy Leather, Black Action Leather and TPU	
	Toe Cap : Steel	
	Midplate : Composite	
	Midsole : Static Dissipative EVA	
	Outsole : Static Dissipative Nitrile Rubber (NBR)	
Footwear only Resistance	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM9.1
Footwear System Resistance	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM9.1
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM97.1
Color	Upper : Black Midsole : Light Grey Outsole : Black	
Sizes (European)	37, 38, 39, 40, 41, 42, 43, 44, 45, 46 & 47	
Conformity	<ol> <li>The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation (Category: S3 SRC HRO)</li> <li>SNI 7079-2009 (NPB 104-116-170603)</li> <li>CNS 20345: 2015 (R3B081)</li> </ol>	



The values shown above were developed from random samples taken from production material. To the best of our knowledge, we believe them to be typical for the product. However actual values may vary somewhat from those depicted here and Dou Yee Enterprises makes no warranty, expressed or implied, as to the suitability of these materials for any specific use. Customers should determine product suitability based upon their own internal criteria.

Date: 2020 / 2021